

Products ▾

Assemble kit

**B** TurretCam HL

More ▾

## Tech specs

**B**ASELINE

# TurretCam HL (8 Mp/2.8 mm)

Wired AI-powered security IP camera with a 110° viewing angle, hybrid illumination, True WDR, microphone, and PoE/12 V. For outdoor and indoor use.



---

## Camera

### Image sensor

8 MP CMOS, 1/2.7" type

### Lens focal length

2.8 mm

## Maximum aperture

f/1.6

## Lens iris type

fixed

## Lens focal type

fixed

## Field of view

horizontal: 110°

vertical: 56°

diagonal: 126°

## DORI distance

- Detection: 90 m
- Observation: 36 m
- Recognition: 18 m
- Identification: 9 m

## Maximum illumination distance

- white LED: up to 50 m
- IR LED: up to 50 m

Intelligent lighting control automatically adjusts the intensity of IR and white LEDs in real time to prevent overexposure. This ensures clear visibility of objects at varying distances – whether close to or far from the camera – in low-light conditions.

## Minimum illumination

color: 0.005 lx

B/W: 0 lx

## Signal-to-noise ratio (SNR)

more than 52 dB

---

## Video

### Resolution

- 8 MP (3840 × 2160)
- 6 MP (3072 × 1728)
- 5 MP (2944 × 1656)
- 5 MP (2880 × 1620)
- 5 MP (2592 × 1944)
- 4 MP (2560 × 1440)
- 3 MP (2304 × 1296)
- 2 MP (1920 × 1080)
- 0.6 MP (1024 × 576)

### Frame rate

up to 20 fps

### Image rotation

0°, 180°

### Video codec

H.265, H.264

## Dynamic range

120 dB (True WDR)

## Storage

microSD

### Ajax NVR

Camera supports microSD up to 256 GB. The memory card should be Class V30 or faster. The card is not included in the complete set.

---

## Audio

### Built-in microphone

With the corresponding settings, the camera can record audio at the scene.

### Audio codec

G711-ULAW, G711-ALAW, G726, G722

---

## Intelligent video analytics

### Motion detection

The camera detects motion using software image frame analysis.

## AI object detection

People

Pets

Vehicles

---

## Network

### Port

1 × RJ-45 self-adaptive Ethernet (10/100 Mbps)

### Protocol

HTTP, HTTPS, TCP/IP, IPv4, IPv6, SNMP, RTSP, UDP, DHCP, DNS, DDNS

### Interoperability

ONVIF (Profile S/T\*)

Ajax cameras and NVRs can be integrated into third-party video management systems (VMS).

\* Profile T is supported for basic streaming and configuration. Advanced features such as metadata, event handling, or edge recording may not be available.

[Learn more](#) >

---

## Key features

## Video protocol

### JetSparrow

Fast and encrypted peer-to-peer video protocol developed by Ajax Systems.

## Visual verification of Ajax alarms

The system allows you to configure a scenario according to which Ajax detectors trigger selected cameras to start recording. The recorded event is immediately delivered to the mobile or desktop monitoring app.

## Privacy

Advanced privacy controls ensure a high level of personal data protection. All access rights – including those for mobile app users, installers, and monitoring company operators via Ajax PRO Desktop – are fully configurable by the device owner. This guarantees that only authorized parties can access video streams, event history, or device settings, in accordance with the owner's preferences.

---

## Sabotage protection

### mTLS

Encrypted connection for data protection.

### Authentication

via Ajax Cloud

### Secure Boot

Protection against firmware spoofing.

## OTA signature verification

Secure automatic firmware update.

---

## Power supply

### PoE standard

802.3at/af

### PoE power consumption

- maximum: up to 8.3 W
- average: up to 7.7 W

### Power supply unit

12 V<sub>DC</sub> ± 20%, 1 A

### 12 V DC power consumption

- maximum: up to 7.1 W
  - average: up to 6.6 W
- 

## Enclosure

## Dimensions

103 × 98 × 98 mm

## Weight

475 g

## Operating temperature range

from -30 °C to +60 °C

## Operating humidity

up to 90%

## Protection class

IP65, IK08



---

## Color

Black



White



## Complete set

TurretCam HL (8 Mp/2.8 mm)

Installation template

Installation kit

Quick start guide

## Certification and compliance with standards



TurretCam HL (8 Mp/2.8 mm)



## Additional information

**Compliance with standards**

**Learn more** >

**User manual**

**Learn more** >

**Warranty**

24 months

**Learn more** >

## Subscribe

Subscribe to our emails about secure life. No spam.



## Request extra help

✉ support@ajax.systems

📧 @AjaxSystemsSupport\_Bot

💬 Send a request



Rating 4.8

4,000,000

people worldwide under Ajax protection

💡 Suggest a feature




## Products

- Intrusion protection
- Video surveillance
- Fire and life safety
- Comfort and automation
- All products
- Services
- System integrations
- Ajax Ready products
- Fibra wired protocol
- Ajax radio protocols

## Software

- Ajax Security System
- Ajax PRO: Tool for Engineers
- Ajax Desktop
- Ajax PRO Desktop
- Ajax TV
- Ajax Translator PRO
- Ajax Cloud Signaling
- Scenarios



## Solutions

Customer stories

## Support

Manuals and articles

[Solutions by facility type](#)

[Commercial fire detection and alarm system](#)

[Wireless Grade 3 solution](#)

[Upgrades and retrofits](#)

[Why Ajax](#)

[How it works](#)

[Compliance with standards](#)

## Tools

[Ajax device compatibility](#)

[CMS software compatibility](#)

[Video storage calculator](#)

[Video device calculator](#)

[Battery life calculator](#)

[Radio communication range calculator](#)

[Switches and outlets configurator](#)

[Fibra power supply calculator](#)

[All web tools](#)

## Monitoring solutions and integrations

[Intrusion alarm monitoring](#)

[Video monitoring and visual alarm verification](#)

[Audio alarm verification](#)

## Company

[Blog](#)

[About us](#)

[Press page](#)

[Events](#)

[Career](#)

[Ajax Next](#)

[Students at CES 2026](#)

[Reviews and feedback](#)

## For partners

[For partners](#)

[Ajax Academy](#)

[Partner Portal](#)

[🇩🇰 Denmark](#) [Privacy policy](#) [Report a vulnerability](#) [GDPR White Paper](#) [NDAA Statement](#) [Cookie policy](#)

[Anti-Spam Policy](#) [Ajax Services T&C](#) [End user agreement](#) [Warranty](#)

© 2026 AJAX SYSTEMS CH. All rights reserved