# LVF-5005N-S1250 Varifocal lens, 12-50mm, 5MP, C mount

www.boschsecurity.com





- ► High-quality optics
- ▶ Reliable, robust construction
- ► Focal length options

As surveillance cameras can now capture even higher picture resolutions through the use of HD sensor technology and advanced processing, the lenses also need to have an optical resolution that allows the camera to work at its optimal point.

This lens is designed to provide improved image resolution and sharpness, and better depth of field.

### System overview

This lens comes with a standard C mount for use with a variety of cameras.

The DC-iris control connection is a four-pin standard plug that fits directly into the camera's iris output. This lens delivers impressive optical quality due to its megapixel resolution, contrast reproduction, and coating.


The mechanical construction is designed to withstand both frequent iris control operations and the environmental stress of security installations. It provides long and reliable operation with no maintenance.

For flexible, high-quality, reliable lenses that match an HD camera's performance, this lens is the ideal solution.

# **Certifications and approvals**

Region	Regula	tory compliance/quality marks
Europe	CE	LVF-5005N-S1250

# Installation/configuration notes



4-pin iris connector

Pin 1: Damping coil -Pin 2: Damping coil + Pin 3: Driving coil + (open) Pin 4: Driving coil -

# Parts included

Quantit y	Component
1	Unit

## **Technical specifications**

LVF-5005N-S1250		
Maximum sensor format	1/1.8-inch	
Optical resolution	5 Megapixels	
Focal length	12 - 50 mm	
Iris range	F1.8 to T360	
Min object distance	0.8 m (2.63 ft)	
Back focus distance (values in air)	10.19 mm (wide), 10.12 mm (tele) values in air	
Weight	175 g (0.386 lb)	
Dimensions	Ø 52.4 mm x 89.3 mm	
Lens mount	С	
Angle of view (HxV)	20.9 x 15.7° Wide	

LVF-5005N-S1250		
1/3-inch sensor 4:3	5.3 X 4 Tele	
Angle of view (HxV) 1/3-inch sensor 16:9	24.1 x 13.5° Wide 6.1 x 3.4° Tele	
Angle of view (HxV) 1/2.7-inch sensor 16:9	26.6 x 14.9° Wide 6.7 x 3.8° Tele	
Angle of view (HxV) 1/1.8-inch sensor 16:9	33.2 x 18.6° Wide 8.3 x 4.7° Tele	
Iris control	4-pin, DC control	
Focus ctrl	manual	
Zoom ctrl	manual	
IR corrected	yes	
Environmental		
- Operating Temperature	-10°C to+50°C (+14°F to +122°F)	
- Storage Temperature	-20°C to +60°C (-4°F to + 140°F)	
- Operating Humidity	35% to 90% non-condensing	

### **Ordering information**

### LVF-5005N-S1250 Varifocal lens, 12-50mm, 5MP, C mount

Varifocal megapixel IR corrected lens with 1/1.8" sensor max and C-mount Order number LVF-5005N-S1250

### Represented by:

Europe, Middle East, Africa: Bosch Security Systems B.V. Boscn Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 emea.securitysystems@bosch.com emea.boschsecurity.com

Germany: Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Germany www.boschsecurity.com

North America:

North America: Bosch Security Systems, LLC 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2609
apr.securitysystems@bosch.com www.boschsecurity.asia