## **HIKVISIO**N

# **DS-PD2-T12P-WEL**

**Wireless Outdoor Dual-Tech Detector** 

DS-PD2-T12P-WEL delivers long range signaling, multi-award-winning two-way wireless technology, heightened false alarm immunity with Dual-Vision Pet Immune detection technology, as well as a host of features that make this a steadfast detector that's quick and easy to install. Offering 90° detection (install between 1 - 1.5m), the brand-new DS-PD2-T12P-WEL can provide a maximum detection range of 12m.



#### AVAILABLE MODEL

DS-PD2-T12P-WEL	Wireless Outdoor Dual-Tech Detector
DS-PDB-EX-Wall bracket	Wall bracket (Need to order separately )
DS-PDB-EX-Adapter	Detector Bracket for Extending coverage angle to 90 degrees (Need to
	order separately, using together with DS-PDB-EX-Wall bracket)
DS-PDB-EX-Fixed bracket	Fix two external detectors to give added coverage to perimeters (Need
	to order separately)

\*All bracket need to order separately.

### MAIN FEATURES

- Microwave + 2 independent PIR
- Detection Range : 12m with Volumetric coverage 90  $^{\circ}$
- Alarm: Tamper Alarm, Intruder Alarm
- Adjustable PIR/MW range
- Dual-Vision Pet Immune (up to 24kg)
- Anti-Sway Analytics
- Blue Wave Technology
- IP55 Heavy Duty Design

#### SPECIFICATION

Wireless Outdoor Dual-Tech Detector		
Detection Range	12m, detection angle: 90°	
Detection Speed	0.25m/s ~ 3m/s	
Animal Immunity	Up to 24kg	
Power Supply	2 × 3V 4700mAH Lithium Battery packs,	
	up to 3 years Battery life	
<b>Operation Temperature</b>	-20°C ~ +70°C	
Dimension(L*W*H)	188mm*77mm*84mm	
Weight	300g (without bracket)	
Installation Environment	Outdoor	
Installation Height	1-1.5m	
Transmission Frequency	868MHz	
Transmission Range	800m	